

Package: pps (via r-universe)

October 31, 2024

Version 1.0

Date 2021-01-14

Title PPS Sampling

Author Jack G. Gambino <jack.gambino@gmail.com>

Maintainer Jack G. Gambino <jack.gambino@gmail.com>

Description Functions to select samples using PPS (probability proportional to size) sampling. The package also includes a function for stratified simple random sampling, a function to compute joint inclusion probabilities for Sampford's method of PPS sampling, and a few utility functions. The user's guide pps-ug.pdf is included in the ../pps/doc directory. The methods are described in standard survey sampling theory books such as Cochran's ``Sampling Techniques"; see the user's guide for references.

License GPL (>= 2)

NeedsCompilation no

Date/Publication 2021-01-17 05:50:02 UTC

Repository <https://jack-gambino.r-universe.dev>

RemoteUrl <https://github.com/cran/pps>

RemoteRef HEAD

RemoteSha c821badfa94fb75a8cc75f6ab6a407450e002da0

Contents

| | |
|-----------------|---|
| calif | 2 |
| califcty | 2 |
| permuteinstrata | 2 |
| pps1 | 3 |
| ppss | 4 |
| ppssstrat | 4 |
| ppswr | 5 |
| sampford | 6 |

| | |
|------------------------|---|
| sampfordpi | 6 |
| sizesok | 7 |
| stratsrs | 8 |
| stratumsizes | 8 |

Index **10**

calif *California places*

Description

See user's guide

Note

See the user's guide, pps-ug.pdf, for more information.

califcty *California counties*

Description

See user's guide

Note

See the user's guide, pps-ug.pdf, for more information.

permuteinstrata *Randomize units within strata*

Description

Randomize the order of units within each stratum

Usage

permuteinstrata(stratsizes)

Arguments

stratsizes A vector containing the size of each stratum

Value

Returns the vector of permuted indices. In the example below, the returned vector has 29 elements.

Note

See the user's guide, pps-ug.pdf, for more information.

Examples

```
stratsizes <- c(9,10,10) # strata have 9, 10 and 10 units, respectively
permuteinstrata(stratsizes)
```

pps1

Select one unit with PPS

Description

Use PPS systematic sampling to select a single unit out of N

Usage

```
pps1(sizes)
```

Arguments

sizes A vector of the sizes of the units in the population

Value

Returns the index of the unit that was selected

Note

See the user's guide, pps-ug.pdf, for more information.

Examples

```
sizes <- c(9,2,5,17,4,21,15,7,4,11,23,23,14)
sampleindex <- pps1(sizes)
```

ppss *PPS systematic sampling*

Description

Use PPS systematic sampling to select a sample of n units out of N

Usage

```
ppss(sizes, n)
```

Arguments

| | |
|-------|--|
| sizes | A vector of the sizes of the units in the population |
| n | The sample size |

Value

Returns the indices of the units that were selected in the sample

Note

See the user's guide, [pps-ug.pdf](#), for more information.

Examples

```
sizes <- c(9,2,5,17,4,21,15,7,4,11,23,23,14)
sampleindices <- ppss(sizes,4)
```

ppssstrat *Stratified PPS systematic sampling*

Description

In each stratum, select a sample using pps systematic sampling

Usage

```
ppssstrat(sizes, stratum, n)
```

Arguments

| | |
|---------|---|
| sizes | A vector of the sizes of the units in the population, sorted by stratum |
| stratum | A vector of stratum codes, in the same order |
| n | A vector containing the sample size in each stratum |

Value

Returns the indices of the units that were selected in the sample

Note

ppssstrat calls pps once per stratum. See the user's guide, pps-ug.pdf, for more information.

Examples

```
sizes <- c(1:5,10:6)*10
strat <- c(1,1,1,2,2,3,3,3,3,3)
n <- c(2,1,3)
ppssstrat(sizes,strat,n)
```

ppswr

PPS sampling with replacement

Description

Use PPS sampling to select a sample of n units out of N with replacement

Usage

```
ppswr(sizes,n)
```

Arguments

| | |
|-------|--|
| sizes | A vector of the sizes of the units in the population |
| n | The sample size |

Value

Returns the indices of the units that were selected in the sample

Note

See the user's guide, pps-ug.pdf, for more information.

Examples

```
sizes <- c(9,2,5,17,4,21,15,7,4,11,23,23,14)
sampleindices <- ppswr(sizes,4)
```

sampford

Sampford's PPS sampling method

Description

Use Sampford's method to select a PPS sample of units

Usage

```
sampford(size,n)
```

Arguments

| | |
|------|--|
| size | A vector of the sizes of the units in the population |
| n | The sample size |

Value

Returns the indices of the units that were selected in the sample

Note

The function `sampfordpi` can be used to compute joint inclusion probabilities for this method. See the user's guide, `pps-ug.pdf`, for more information.

Examples

```
size <- c(9,2,5,17,4,21,15,7,4,11,23,23,14)
sampleindices <- sampford(size,4)
```

sampfordpi*Joint inclusion probabilities for Sampford's PPS sampling method*

Description

Compute joint inclusion probabilities for Sampford's method of PPS sampling

Usage

```
sampfordpi(sizes,n)
```

Arguments

| | |
|-------|--|
| sizes | A vector of the sizes of the units in the population |
| n | The sample size |

Value

Returns a matrix with the inclusion probability $\pi_i(i)$ for each unit i in the population and with the joint inclusion probability $\pi_i(i,j)$ of units i and j in position (i,j) in the matrix, where i and j are not equal. Note that the size of the matrix is $N \times N$, where N is the population size.

Note

The function `sampford` can be used to select a sample using Sampford's method. See the user's guide, `pps-ug.pdf`, for more information.

Examples

```
sizes <- c(9,2,5,17,4,21,15,7,4,11,23,23,14)
piij <- sampfordpi(sizes,4)
weights <- 1/diag(piij) # the weights one would use for estimation
```

sizesok

Check that unit sizes are not too big

Description

See user's guide

Usage

```
sizesok(size,n)
```

Arguments

`size` A vector of the sizes of the units in the population
`n` The sample size

Value

Returns the number of 'bad' units

Note

See the user's guide, `pps-ug.pdf`, for more information.

| | |
|----------|--|
| stratsrs | <i>Stratified simple random sampling</i> |
|----------|--|

Description

In each stratum, select a simple random sample

Usage

```
stratsrs(stratum,nh)
```

Arguments

| | |
|---------|---|
| stratum | A vector of stratum codes, sorted by stratum |
| nh | A vector containing the sample size in each stratum |

Value

Returns the indices of the units that were selected in the sample

Note

See the user's guide, pps-ug.pdf, for more information.

Examples

```
strat <- c(1,1,1,1,1,2,2,2,3,3,3,3,3,3) # stratum 1 has 5 units, etc.  
nh <- c(2,1,3) # select 2 units from stratum 1, 1 from stratum 2 and 3 from 3  
stratsrs(strat,nh)
```

| | |
|--------------|-------------------------------------|
| stratumsizes | <i>Compute size of each stratum</i> |
|--------------|-------------------------------------|

Description

Given a vector of sorted stratum indicators, returns the number of units in each stratum

Usage

```
stratumsizes(stratum)
```

Arguments

| | |
|---------|---------------------------------------|
| stratum | A vector of sorted stratum indicators |
|---------|---------------------------------------|

Value

Returns the number of units in each stratum

Note

See the user's guide, [pps-ug.pdf](#), for more information.

Index

* survey

- calif, 2
- califcty, 2
- permuteinstrata, 2
- pps1, 3
- ppss, 4
- ppssstrat, 4
- ppswr, 5
- sampford, 6
- sampfordpi, 6
- sizesok, 7
- stratsrs, 8
- stratumsizes, 8

- calif, 2
- califcty, 2

- permuteinstrata, 2
- pps1, 3
- ppss, 4
- ppssstrat, 4
- ppswr, 5

- sampford, 6
- sampfordpi, 6
- sizesok, 7
- stratsrs, 8
- stratumsizes, 8